



SLIMLINE

Vertical Blind System

SLIMLINE

Vertical Blind System

HARDWARE SPECIFICATION



Vertical blinds should be manufactured using the Slimline headrail system with aluminium headrail of 29.25mm (1 1/32") width and 27.75mm (1 1/32") depth.

The operating units will feature direct gearing for instant operator response and the chain will be either plastic or metal.

There must be an extensive range of top, face and side fixing brackets.

Each of these three types of brackets must offer various options of function to cover almost every fitting situation.

The material used for the louvre will be creased and punched so that a plastic insert can be stitched, glued or sealed into the top of the louvre.

The Slimline vertical blind headrail system will feature a secure hook on the lower part of the carrier truck on to which the insert at the top of the louvre will attach to ensure full integrity of the system.

FABRICS

A wide selection of fabrics are available including blackout, flame retardant and those featuring **spc** Solar Protective Coating.

Flame retardant fabrics can comply with some or all of the following standards:

- FTS17 • DIN4102 B1 & B2 • AFNOR 92-503 • CAN/ULC S109 - M87 • BS5867 1980 Part 2 Type B • BS476 Part 6 Class 0 - Part 7 Class 1
- NFPA701 SMALL & LARGE

A full advisory service is available. If you would like to discuss the Slimline system or have a practical demonstration of it's benefits, please contact your local distributor.

YOUR LOCAL SLIMLINE DISTRIBUTOR IS